

Zaffiro



1171



1177



1178



1652



1118



1163



1659



1651



1186



1721




1165



1176




1638



1870



1634



1117




1198



1718



1158



1647



1677



1179



1673




1226



1129



1180



1121



1181



1639




1649



1135



1159



1626



1648



1133



1660



1661



1173



1124



1122



1619



1152



1149



1616




1656



1172



1174



1609



1131



1607



1137



1662



1136



1627



1140




1187



1147



1112



1216



1141



1101



1631



1621



1127



1632



1674



1658



1653



1156



1145




1643



1105



1154



1633




1650



1116



1108



1113



1657




1110




1655




1115



1119



1120



1160

Caratteristiche tecniche

Pellame	Bovino europeo
Concia	Al cromo
Tintura	All'anilina
Rifinitura	Con pigmenti e resine
Tipologia	Fiore corretto, superficie liscia, opaca e morbida
Superficie media	< 5,00 m ²
Spessore	0,9-1,1 mm

Technical characteristics

Raw material	European bovine hide
Tannage	Chrome tanning
Dyeing	Aniline dyed
Finish	With pigments and resins
Leather type	Top-grain leather, smooth, matt and soft surface
Average size	< 54.00 SqFt
Thickness	0.9-1.1 mm

Zaffiro standards

• Solidità del colore allo strofinio a secco Dry rubbing fastness	(UNI EN ISO 11640)	500 cicli ≥ 4 Scala grigi 500 cycles ≥ 4 Grey scale
• Solidità del colore allo strofinio a umido Wet rubbing fastness	(UNI EN ISO 11640)	250 cicli ≥ 3/4 Scala grigi 250 cycles ≥ 3/4 Grey scale
• Solidità del colore allo strofinio con sudore alcalino Alkaline perspiration rubbing fastness	(UNI EN ISO 11640)	80 cicli ≥ 3/4 Scala grigi 80 cycles ≥ 3/4 Grey scale
• Resistenza alla luce, lampada ad arco di Xenon Light fastness to artificial Xenon light	(UNI EN ISO 105 B02)	≥ 5 Scala dei blu ≥ 5 Blue scale
• Adesione della rifinitura Adhesion of finish	(UNI EN ISO 11644)	≥ 2,5 N/Cm
• Resistenza alla flessione Flexing endurance	(UNI EN ISO 5402)	>50.000 Cicli nessun danno >50,000 Cycles no damage
• Resistenza allo strappo pantalone Tear strength – Single edge tear	(UNI EN ISO 3377-1)	≥ 20 N
• Reazione al fuoco Burning behavior	(EN 1021-1/2) (BS 5852-1/2) (TB 117:2013) (IMO RES A652[16])	Passa il test Pass